


HDVR81080-Q2 / HDVR161080-Q2

8 / 16 Camera 1080P 5-Way DVR







Easy Playback Calendar Search & Selectable Time Bars.



Recording Schedule Set Times, Dates & Camera Options



Mobile / Remote Access Access DVR Using Optiview VMS & Mobile Apps.



Ample Storage 2 HDD Bay for up to 12TB of Internal Storage.

Overview

The HDVR81080-Q2 & the HDVR161080-Q2 5-Way DVRs are an all-in-one recording solution that supports HD-over-Coax, AHD, TVI, Analog and IP cameras using RG59, CAT5/6 or Fiber cables. These DVRs record up to 1080P (Real-Time) with up to 4 MP playback. They have 4 RCA audio inputs and a single output which supports Two-way Talk. There is plenty of room to record with a storage capacity of up to 12TB.

Features

- Support HD-over-Coax, AHD, TVI, Analog & IP Video Input
- 1080P Real-Time Recording
- 8 / 16 Channel Sync Real-Time Playback
- 1080P Video Output (HDMI, VGA)
- View Remotely over Web, Free Optiview VMS or Mobile Apps

Specifications

Model		HDVR81080-Q2	HDVR161080-Q2
Main Processor / Operating System		Embedded Processor / Embedded LINUX	
Video Input	Analog / HD-over-Coax	8 × BNC	16 × BNC
	IP / Network	8 + 4 up to 5MP	16 + 8 up to 5MP
Video Output		1 × HDMI, 1 × VGA	
Audio (Input / Output)		$4 \times RCA / 1 \times RCA$	
Two-way Talk		Reuse Audio Channel 1 (Input / Output)	
Video Standards		Analog: NTSC (525 TV Lines @ 60 fps), PAL (625 TV Lines @ 50 fps), HD-over-Coax: 1080P, 720P, IP / Network: 5MP, 1080P, 720P, D1, CIF	
Display Resolution		1920 × 1080 / 1280 × 1024 / 1280 × 720 / 1024 × 768 / 800 × 600	
Display Split		1/4/8/9/16	1/4/8/9/16/25
Playback Channels		1/4/9	1/4/9/16
Playback Functions		Play, Pause, Stop, Rewind, Fast Play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom	
Recording Resolutions		1080P (1920×1080) / 720P (1280×720) / 960H (960×576 / 960×480) / D1 / 4CIF (704×576 / 704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)	
Recording Speed (Main Stream)		1080P / 720P / 960H / D1 / HD1 / 2CIF / CIF (1~25/30fps)	
Compression (Video / Audio)		H.264+ / H.264 / G.711	
Recording Bit Rate		1~6144Kb/s per Channel	
Recording Mode		Manual, Schedule [(Regular / Continuous), MD], Stop	
Trigger Events		Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer, Screen Tips	
Motion Detection		MD Zones: 396 (22 $ imes$ 18), Video Loss, Camera Blank	
Alarm Input / Relay Output		8/3	16/3
Search Mode		Time / Date, MD & Exact Search (Accurate To Second)	
HDD Bays / Storage Capacity		2 / 12TB (SATA - Internal)	
Backup Mode		USB Device & Network	
USB 2.0 / 3.0		1 Front / 1 Rear	1 Front / 1 Rear
RS485		1 (PTZ Control)	
RJ-45 (Ethernet)		1 (10/100/1000 Mbps)	
Network Functions		HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP, Alarm Server, P2P, IP Search	
Max. User Access		128 Users	
Power (Supply / Consumption)		12V DC, 4A / 15 W (without HDD)	12V DC, 5A / 15 W (without HDD)
Working Environment		$14^{\circ} \sim 131^{\circ} \text{ F, } 10 \sim 90\% \text{ RH, } 86 \sim 106 \text{ kpa}$	
Dimensions (W×D×H) / Weight		1U, 14.8" × 11.3" × 2.17" / 5.18 lbs (without HDD)	