

IP5MIAD-49

5 Megapixel IP / Network Armor Dome Camera



HD Resolution



PoE Compatible



Mobile Access



Weatherproof

Features

- 1/2.5" 3 Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Max 12fps @ 5M (2560 x 1920) & 25/30fps @ 1080P (1920x1080)
- DWDR, Day/Night(ICR), 3DNR, Auto Iris, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 4~9mm varifocal lens
- Max. IR LEDs Length 20m / 65 ft
- Micro SD Memory Card
- IP66, IK10, PoE



Specifications

IP5MIAD-49		
Image Sensor	1/2.5" 5 MegaPixel Aptina CMOS	
Resolution	5M (2560 x 1920) / 1080P (1920x1080) / 720P (1280x720) / D1 (704x576/704x480) / CIF (352x288/352x240)	
Frame Rate	Main Stream	5M (1~12fps) / 1080P/720P (1~25/30fps)
	Sub Stream	D1/CIF (1~30fps)
Bit Rate	32K ~ 8192Kbps	
Electronic Shutter	Auto / Manual ; 1/3~1/10,000	
Effective Picture (H x V)	2560 x 1920	
Focal Length	4~9mm varifocal lens	
Lens Mount Type	Board-in Type	
Min. Illumination Color / B&W	Color: 0.01Lux / F1.6	
Infrared Range	65ft. (Max.)	
Day / Night	Auto (ICR) / B&W / Color	
Backlight Compensation	BLC / HLC / DWDR	
White Balance	Auto / Manual	
Gain Control	Auto / Manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 Areas	
Angle of View	H: 86.5°~28.6°	
Network	1 x RJ45 Ethernet port (10/100Base-T)	
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
Compatibility	ONVIF, PSIA, CGI	
Memory Slot	Micro SD, Max 64GB	
Audio	1 / 1 channel In / Out	
Max User Access	20 Users	
Weatherproof Rating	IP66	
Power Supply	DC12V / AC24V, PoE(802.3af)	
Power Consumption	<8.5W (AC24V: +2W)	
Working Environment	-22°~140° F (-30°~ 60° C), 10%~90% RH	
Dimensions / Weight	5.9" x 4.7" (151mm x 119mm) / Approx 2.8 lbs	